

Datasheet



- Connects Sure Cross® 1-wire serial sensors to a Windows PC USB port and supplies power to the sensor
- Supports baud rates of 9600, 19200, and 38400
- Converts a 1-wire serial interface with a M12 connector to USB
- Supports 32-bit and 64-bit configurations of Windows XP, Windows 7, Windows 10, and Windows Vista
- Download the free [Sensor Configuration Software](#)

Model: **BWA-USB1WIRE-001**—1-wire serial interface to USB, 1 meter long

When plugging this cable into your computer for the first time, give the cable one to two minutes to check your computer for the proper driver, download the driver, then install it. When the cable is ready for use, the green LED will be on. Plug the cable into your 1-wire serial sensor. The cable should then supply enough power to the sensor to configure it. For additional information, updated documentation, and a list of accessories, refer to Banner Engineering's website, www.bannerengineering.com.

5-pin M12 Female Connection

Table 1: 5-pin M12 female connection wiring

5-pin M12 Female Quick Disconnect	Pin	Wire Color	Sensor Wiring
	1	Brown	5 V DC
	2	White	not used
	3	Blue	DC common (GND)
	4	Black	not used
	5	Gray	1-wire serial communication

Specifications

Input Power

5 V DC from USB port

Current

5 mA at the PC, single sensor (not intended to power multiple Banner sensors)

Operating Parameters

–40 °C to +80 °C (–40 °F to +176 °F)
95% maximum relative humidity (non-condensing)

USB

Connector: USB type A plug
Standard: 2.0

1-Wire Serial Interface

9.6k, 19.2k (default), or 38.4k; 8 data bits; 1 stop bit; no parity (default), even parity, or odd parity
Connector: M12 connector compatible with Banner FlexPower Node with Serial Interface, 5 V DC power output

1-Wire Serial Sensors

M12FTH4Q Temperature and Humidity Sensor
M12FT4Q Temperature Sensor
QM30VT1 Vibration and Temperature Sensor
K50UX1ARA and **K50UX1CRA** U-GAGE K50U Ultrasonic Sensor

Length

1 meter (This cable can be extended up to 30 meters.)

Banner Engineering Corp. Limited Warranty

Banner Engineering Corp. warrants its products to be free from defects in material and workmanship for one year following the date of shipment. Banner Engineering Corp. will repair or replace, free of charge, any product of its manufacture which, at the time it is returned to the factory, is found to have been defective during the warranty period. This warranty does not cover damage or liability for misuse, abuse, or the improper application or installation of the Banner product.

THIS LIMITED WARRANTY IS EXCLUSIVE AND IN LIEU OF ALL OTHER WARRANTIES WHETHER EXPRESS OR IMPLIED (INCLUDING, WITHOUT LIMITATION, ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE), AND WHETHER ARISING UNDER COURSE OF PERFORMANCE, COURSE OF DEALING OR TRADE USAGE.

This Warranty is exclusive and limited to repair or, at the discretion of Banner Engineering Corp., replacement. **IN NO EVENT SHALL BANNER ENGINEERING CORP. BE LIABLE TO BUYER OR ANY OTHER PERSON OR ENTITY FOR ANY EXTRA COSTS, EXPENSES, LOSSES, LOSS OF PROFITS, OR ANY INCIDENTAL, CONSEQUENTIAL OR SPECIAL DAMAGES RESULTING FROM ANY PRODUCT DEFECT OR FROM THE USE OR INABILITY TO USE THE PRODUCT, WHETHER ARISING IN CONTRACT OR WARRANTY, STATUTE, TORT, STRICT LIABILITY, NEGLIGENCE, OR OTHERWISE.**

Banner Engineering Corp. reserves the right to change, modify or improve the design of the product without assuming any obligations or liabilities relating to any product previously manufactured by Banner Engineering Corp. Any misuse, abuse, or improper application or installation of this product or use of the product for personal protection applications when the product is identified as not intended for such purposes will void the product warranty. Any modifications to this product without prior express approval by Banner Engineering Corp will void the product warranties. All specifications published in this document are subject to change; Banner reserves the right to modify product specifications or update documentation at any time. Specifications and product information in English supersede that which is provided in any other language. For the most recent version of any documentation, refer to: www.bannerengineering.com.

For patent information, see www.bannerengineering.com/patents.

